




## M12 Female Panel, PCB Type, Rear fastened, K-coding

- Connector series: M12
  - Gender: Female
  - Coding: K
  - Locking type: Fix screw
  - Mounting type: Rear fastened
  - Part No.: MB12FBKRF05ST-X
- X refers to Chasis-side thread size



### ■ General information

Standard:	IEC 61076-2-111
Ambient temperature:	-40°C ~ +80°C (fixed installation) -20°C ~ +80°C (flexible installation)
Connector insert:	PA
Connector contacts:	Brass with gold plated
Connector nut/screw:	Brass with nickel plated
Seal / O-ring:	FKM

Insulation resistance:	≥ 100MΩ
Contact resistance :	≤ 8mΩ
Shielding:	Unavailable
IP rating:	IP68 in locked condition
Mating endurance:	>500 cycles

### ■ Electrical data & Mechanical data

Contacts	Contacts termination	Rated current	Voltage		Wire gauge / size		Part No.
			A/C	D/C	AWG	mm <sup>2</sup>	
05 pins  (4+PE)	PCB	16A	690V	NC	14AWG	2.0	MB12FBKRF05ST-X

Note: X refers to Chasis-side thread size

### ■ Remarks

- Please refer to Page 578 for the Conversion between American Wire Gauge AWG and Wire Cross-section mm<sup>2</sup>.
- Please refer to Page 96 for products' part number encoding rule.